

DR40SG-WH/BK/SN

4inch LED Square Gimbal Ultra Slim
Recessed downlight(Air tight)

Job Information		
Project Name		Type
Location		
Quantity		Date
Contact/ Name		
Notes		

Body

- Durable airtight aluminum
- White polycarbonate diffuser lens for low glare

LED Characteristics

- 9-Watt LED Module
- Minimal heat emission
- Up to 860 Lumens
- Superior LED Performance and lifespan
- Excellent Color rendering with Spotlight

Dimming

- 10%-100% dimming capability
- Compatible with industry TRIAC/ELV dimmers (contact factory for compatible dimmers list)

Environment

- Suitable for damp locations
- Suitable for insulated ceiling application
- Can be installed indoor and for outdoor applications

Mounting

- Included two springs loaded clips to attach to any ceiling material
- The slim profile allow to be mounted dock work

Description

• DR40SG, a 9watt 4-inch All CCT slim profile square flat LED panel is a high-performance, easy to install downlight. It offers excellent light output, energy efficiency, and streamlined design. Suitable for damp location and use in soffits.

Beam Spread

- 38 degree beam spread

LED Driver

- Extruded aluminum junction box with integrated 210mA dimmable driver included
- Class II electronic LED driver with 100-125V AC input; includes an 12" cable from driver to fixture

Quick Connect Push-in Terminals

- Three "Quick Connect" Push-in terminals for fast and easy wiring


Operating Temperature

- -20°C - 40°C (-4°F - 104°F)



SPECIFICATION

Application	Ceiling Recessed Mount	Energy Star	YES
Approved Location	Damp	Input	100-125V AC, 60Hz, 0.09A
Beam Angle	38	LM 79	YES
CCT	2700K/3000K/3500K/4000K/5000K	LM 80	YES
Certification	cETLus	Lumens	Up to 860
Class II	YES	Lumens per Watt	95.6
Color	White	Power Factor	>0.95
CRI	80+	Projected Life	5 Years
Dimming	YES	Wattage	9 Watt
Dimming Tech	TRIAC/ELV	Cut-Size	4 1/4"



Zotia International Trade Ltd.
201 Rowntree Dairy Road
Woodbridge, ON, L4L 8B8

T: 905-669-1966
F: 905-851-5262

E: sales@zotia.ca
W: www.dawnray.ca

