DRBL1440

1x4 Back-Lid Wide Voltage Panel Light with 3CCT Selectable

Job Information			
Project Name		Type	
Location			
Quantity		Date	
Contact/ Name			
Notes			

Body

- Durable airtight aluminum
- White polycarbonate diffuser lens for low glare

LED Characteristics

- 40-Watt LED Module
- · Minimal heat emission
- 4400 Lumen output
- Superior LED Performance and lifespan
- · Ideal illumination for commercial

Dimming


- 10%-100% dimming capability
- Flicker-free with 0-10v dimmer

Mounting

- Recessed direct to T-bar ceiling
 Hanging with aircraft cable

Description

• -The DRBL-Series is a wide voltage and high-performance LED flat panel that uses a back-lit design to provide a longer lasting lighting solution that replaces traditional fluorescent lighting.



• -20 C - 40 C (-4°F - 104°F)













SPECIFICATION				
Lumen Output	4400 Lumen	Voltage	100-347 VAC	
Beam Angle	110	Application	T-bar ceiling, hanging	
CCT	3500K/4000K/5000K	Dimming	YES	
Lifetime	>50,000 Hours	Dimming Tech	0-10V	
CRI	82	DLC	YES	
Power	40W	Warranty	5 Years	
Efficacy	110 lm/W	IC Rated	YES	

